

showlabHD™

Specifications

Type:	X 163232	M 060808
Audio:	16x 48 kHz 24-bit *	8x 48 kHz 24-bit
Time based (synchronized):	YES	YES
Logical or by input signal:	optional	---
Video:	1x Full HD 1080 P (16:9) 1600 x 1200px (4:3)	1x Full HD 1080 P (16:9) 1600 x 1200px (4:3)
Time based (synchronized):	YES	YES
Logical or by input signal:	optional	---
Input:	32 channels optocoupler	8 channels optocoupler
Output:	32 channel relays	8 channel relays
Time based (synchronized):	YES	YES
Logical or by input signal:	YES	YES
Seamless transition of audio and video from boarding to main show	YES	YES
User customizable:	YES	YES
Hardware independent:	YES	YES
Assembling:	19" rack module or table-top single unit	Mobile trolley (hand-luggage sized) with 48-pin multi-core plug
Front Panel:	Power On/Off Start / Reset 19" Screen	Emergency Stop Start / Reset Motion Enable LCD Screen
Optional modules:		
More audio channels	•	---
More input channels	•	---
More output channels	•	---
Pre show / Post show modules	•	---
Side effects control	•	---
Remote screening	•	---
Departure monitor	•	---

* Audio: up to 72 channels available optionally • Duration of audio and video files depend on maximum memory size